

FEATURES/BENEFITS

- Pressure-compensating flat emitter guarantees maximum emission uniformity
- Premium resin and UV resistance assures durability and longevity
- Anti-siphoning — eliminates dirt and debris entering the system (CV models)
- Non-draining check valve design means no low-point pooling and simultaneous opening/closing of emitters (CV models)
- 7 ft. check height reduces system runoff (CV models)
- Color-coded stripes to easily identify flow rate
- Banded and shrink-wrapped coils stay intact



STRIPES COLOR CODING



PRODUCT SPECIFICATIONS

Available Flow Rates	0.6 GPH and 0.9 GPH
Emitter Spacing	12 in. and 18 in.
Tubing Dimensions	0.660 in. x 0.560 in. (Outside Diameter x Inside Diameter)

OPERATING SPECIFICATIONS

Operating Range	10 PSI to 58 PSI
Minimum Filtration	120 Mesh
Warranty	7 Years

MAXIMUM RUN LENGTHS

PRESSURE (PSI)	0.6 GPH		0.9 GPH	
	12 in. SPACING	18 in. SPACING	12 in. SPACING	18 in. SPACING
10	189	216	113	165
15	246	316	165	241
20	293	376	197	288
25	328	423	221	324
30	358	460	241	352
35	383	493	258	378
40	406	523	273	400
45	426	549	287	420
50	445	573	300	438
55	462	595	311	459
58	472	607	318	465

PRO-TRADE SKU	DESCRIPTION	EMITTER SPACING	FLOW RATE	CHECK VALVE	LENGTH		
PT-DL17-0912CV-100	Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 100 ft.	12 in.	0.9 GPH	YES	100 ft.		
PT-DL17-0912CV-250	Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 250 ft.			YES	250 ft.		
PT-DL17-0912CV-500	Pro-Trade 17mm Dripline CV 0.9 GPH 12 in. 500 ft.			YES	500 ft.		
PT-DL17-0912PC-100	Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 100 ft.			NO	100 ft.		
PT-DL17-0912PC-250	Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 250 ft.			NO	250 ft.		
PT-DL17-0912PC-500	Pro-Trade 17mm Dripline PC 0.9 GPH 12 in. 500 ft.			NO	500 ft.		
PT-DL17-0612CV-100	Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 100 ft.		12 in.	0.6 GPH	YES	100 ft.	
PT-DL17-0612CV-250	Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 250 ft.				YES	250 ft.	
PT-DL17-0612CV-500	Pro-Trade 17mm Dripline CV 0.6 GPH 12 in. 500 ft.				YES	500 ft.	
PT-DL17-0612PC-100	Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 100 ft.				NO	100 ft.	
PT-DL17-0612PC-250	Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 250 ft.				NO	250 ft.	
PT-DL17-0612PC-500	Pro-Trade 17mm Dripline PC 0.6 GPH 12 in. 500 ft.				NO	500 ft.	
PT-DL17-0918CV-250	Pro-Trade 17mm Dripline CV 0.9 GPH 18 in. 250 ft.	18 in.	0.9 GPH	YES	250 ft.		
PT-DL17-0918CV-500	Pro-Trade 17mm Dripline CV 0.9 GPH 18 in. 500 ft.			YES	500 ft.		
PT-DL17-0918PC-250	Pro-Trade 17mm Dripline PC 0.9 GPH 18 in. 250 ft.			NO	250 ft.		
PT-DL17-0918PC-500	Pro-Trade 17mm Dripline PC 0.9 GPH 18 in. 500 ft.		NO	500 ft.			
PT-DL17-0618CV-250	Pro-Trade 17mm Dripline CV 0.6 GPH 18 in. 250 ft.		18 in.	0.6 GPH	YES	250 ft.	
PT-DL17-0618CV-500	Pro-Trade 17mm Dripline CV 0.6 GPH 18 in. 500 ft.				YES	500 ft.	
PT-DL17-0618PC-250	Pro-Trade 17mm Dripline PC 0.6 GPH 18 in. 250 ft.	NO			250 ft.		
PT-DL17-0618PC-500	Pro-Trade 17mm Dripline PC 0.6 GPH 18 in. 500 ft.	18 in.	0.6 GPH	NO	500 ft.		
PT-DL17-BLNL100	Pro-Trade Dripline Blank 100 ft.			N/A	N/A	N/A	100 ft.
PT-DL17-BLNL250	Pro-Trade Dripline Blank 250 ft.					N/A	250 ft.
PT-DL17-BLNL500	Pro-Trade Dripline Blank 500 ft.	N/A	500 ft.				

